



Para Xylene Specifications

| <i>TYPICAL TEST</i> | <i>UNIT</i> | <i>SPECIFICATIONS</i> | <i>TEST METHOD</i> |
|-------------------------------|---------------|----------------------------------|---------------------|
| <i>PURITY</i> | <i>WT%</i> | <i>99.7 MIN.</i> | <i>ASTM D-3798</i> |
| <i>NON-AR</i> | <i>WT%</i> | <i>0.2 MAX.</i> | <i>ASTM D-3798</i> |
| <i>DISTILLATION RANGE</i> | <i>° C</i> | <i>2 MAX INCLUDING 138.3</i> | <i>D-850</i> |
| <i>T- SULFUR</i> | <i>PPM WT</i> | <i>1 MAX</i> | <i>ASTM D-5453</i> |
| <i>T – CHLORIDE</i> | <i>PPMWT</i> | <i>1 MAX</i> | <i>ASTM D-4929</i> |
| <i>SP.GR AT 15.6 /15.6 °C</i> | | <i>0.8650-0.8661</i> | <i>ASTM D-4052</i> |
| <i>SO2/H2S CONTENT</i> | <i>---</i> | <i>FREE</i> | <i>ASTM D- 853</i> |
| <i>APPEARANCE</i> | <i>---</i> | <i>COLORLESS, CLEAR</i> | <i>VISUAL</i> |
| <i>TOL+BZ</i> | <i>PPM WT</i> | <i>300 MAX</i> | <i>ASTM D-3798</i> |
| <i>ETHYLBENZENE</i> | <i>WT %</i> | <i>0.3 MAX</i> | <i>ASTM D-3798</i> |
| <i>COLOR (PT – CO SCALE)</i> | <i>---</i> | <i>20 MAX</i> | <i>ASTM D- 1209</i> |
| <i>M-XYLENE</i> | <i>WT%</i> | <i>0.25 MAX</i> | <i>ASTM D- 3798</i> |
| <i>O-XYLENE</i> | <i>WT %</i> | <i>0.1 MAX</i> | <i>ASTM D-3798</i> |
| <i>ACID WASH COLOR</i> | <i>---</i> | <i>1 MAX</i> | <i>ASTM D- 848</i> |

Packing : In Bulk